



optimize summary (binary OR object) linker symbol

Search

[Advanced Search](#)

Web

Results 1 - 10 of about 1,450,000 for **optimize summary (binary OR object) linker symbol**. (0.61 seconds)[Show options...](#)

## 1. [Interprocedural Optimization \(IPO\) Overview](#)

You must use the Intel linking tools to **link** mock **object** files. During the compilation process, the compiler first analyzes the **summary** information and then ...

[software.intel.com/sites/products/.../optaps\\_ipo\\_mult.htm](#) - [Cached](#) - [Similar](#)

## 2. [Description of the DUMPBIN utility](#)

/FPO Displays frame pointer **optimization** (FPO) records. ... Specify the 1 argument to display **symbols** in **object** order, along with their offsets. ... Dump of file tracer.exe File Type: EXECUTABLE IMAGE **Summary** 1000 .data 1000 .idata ... for the **linker** (or the /DEBUG and /DEBUGTYPE:COFF options on the command line). ...

[support.microsoft.com/kb/177429](#) - [Cached](#) - [Similar](#)

## 3. [Getting Started - Overview of XL Fortran features](#)

These "r" invocations instruct the compiler to **link** and bind **object** files to ... For a **summary** of **optimization**-related compiler options, see Options for ... A 64-bit **object** or executable that has references to **symbols** from a 32-bit ...

[publib.boulder.ibm.com/infocenter/.../topic...lgs\\_ovr.htm](#) - [Cached](#) - [Similar](#)

## 4. [Linker Output File Qualifiers - HP OpenVMS systems documentation](#)

The body of the compilation **summary** contains information about OPTIONS statement qualifiers ... /**OPTIMIZE**=(**INLINE**=SPEED,LEVEL=4,NOLOOPS,PIPELINE,TUNE=GENERIC,UNROLL=0) ... On **linker** capabilities, default system **object** libraries, and detailed .... The /DEBUG qualifier includes the debugger and places local **symbol** ...

[h71606.www7.hp.com/doc/821ins/6443/6443pro\\_011.html](#) - [Cached](#)

## 5. [Using LD, the GNU linker - Invocation](#)

Here is a **summary** of the options you can use on the ld command line: ... If no **binary** input files at all are specified, the **linker** does not produce any ... instead **optimize** for

memory usage, by rereading the **symbol** tables as necessary. ...

[www.math.utah.edu/docs/info/ld\\_2.html](http://www.math.utah.edu/docs/info/ld_2.html) - [Cached](#) - [Similar](#)

## 6. [LTO\\_Driver - GCC Wiki](#)

Jan 10, 2008 ... **Link** the (single) **optimized object** file. ... The LTO front end ensures that a **symbol** `gnu_lto_v1` is defined in each **object** file so that ...

[gcc.gnu.org/wiki/LTO\\_Driver](http://gcc.gnu.org/wiki/LTO_Driver) - [Cached](#)

## 7. [Runtime Linker in Performance Optimization for Solaris](#)

A filter is a shared library that at **link** time provides only a **symbol** ... The runtime **linker** resolves the library path relative to the **binary** that uses the ...

[developers.sun.com](http://developers.sun.com) > ... > Reference > Technical Articles and Tips - [Cached](#) - [Similar](#)

## 8. [llvm-lld\(1\): LLVM linker - Linux man page](#)

When looking for **objects** specified on the command line, `lld` will ... Library archives (.a files) load only the **objects** within the archive that define **symbols** needed by the output file. ... -help: Print a **summary** of command line options. ... The various -On options will be ignored and no **link** time **optimization** ...

[linux.die.net/man/1/llvm-lld](http://linux.die.net/man/1/llvm-lld) - [Cached](#) - [Similar](#)

## 9. [CS310H - Spring 2007 Lecture 25 - Linking/Loading - real world ...](#)

... **link** and walk through executable module - go back to **optimizing** the code using compiler Can ... **Linker** must resolve references - **Object** modules: include code and ... combining all of the **object** files and resolving relocation and external **symbol** ... but as program gets loaded into memory Next Time: **Review** for quiz.

[userweb.cs.utexas.edu/~fussell/courses/cs310H/lectures/25.txt](http://userweb.cs.utexas.edu/~fussell/courses/cs310H/lectures/25.txt) - [Cached](#)

## 10. [BFD](#)

The **linker** accesses **object** and archive files using the BFD libraries. ... more time and care may be spent **optimizing** algorithms for a greater speed. ... When the **linker** asks for the **symbol** table of an **object** file, it calls through a ...

[www.redhat.com](http://www.redhat.com) > ... > Manuals > Red Hat Enterprise Linux Manuals - [Cached](#)



optimize summary (binary OR object) linker symbol

Search

[Search within results](#) - [Language Tools](#) - [Search Help](#) - [Dissatisfied? Help us improve](#) - [Try Google Experimental](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [Privacy](#) - [About Google](#)